

MANURE SPREADERS

THE SPREADERS WITH THE MOST FEATURES AND BEST WARRANTY IN THE INDUSTRY



Six different spreader models are available. The smaller capacity models are ground wheel driven, the larger models are P.T.O. driven. The Conestoga line of spreaders come standard with a large number of special features.

The best warranty in the industry includes "10 years" on the spreader box. Lifetime on the poly floor and apron chain. Also, these spreaders are covered for the first "3 years" for any defects in workmanship and material.



Distributed by:



13477 Benson Ave. • Chino, CA 91710 Ph: 909/548-4848 • email: sales@gearmore.com

www.gearmore.com




Manure Spreaders

KEY CONESTOGA FEATURES UNAVAILABLE FROM THE COMPETITION ARE:

- "Cor-ten" copper bearing steel is used to provide atmospheric corrosion resistance four times that of plain carbon steel, for longer service life
- Conestoga boxes are of all-welded construction chemically washed, painted with epoxy primer, and finished with a highly corrosion resistant, two-part urethane paint
- All Conestoga spreaders come standard with our own design, stainless steel T-rod apron chain, which provides superior durability and service life
- Beater paddles are a rooster comb design and are bolted on so they can be replaced when wear does occur
- Conestoga spreaders are designed with 12 paddles, more than the competition
- This combination of paddle design and additional paddles improves shredding action and the overall spread pattern

OUTSTANDING FEATURES ALLOWS CONESTOGA TO GIVE THE BEST WARRANTIES IN THE INDUSTRY:

- "10 Years" on the spreader box
- "Lifetime" on the poly floor and apron chain
- "3 Years" for defect in workmanship and material



Stainless Steel T-rod apron chain and poly floor



Replaceable Beater Paddles With Rooster Comb Design



Dolly Wheel Jacks Standard on C-25GD and C-50GD

SPECIFICATIONS:

	C-25GD	C-50GD	C-50 PTO	C-80 PTO	C-125 PTO	C-175 PTO
Capacity	20 cu. ft	38 cu. ft	38 cu. ft	58 cu. ft	85 cu. ft	115 cu. ft
Number of Horses	1-5	4-6	4-6	5-10	10-25	20+
Drive	2-Wheel Ground Drive		540 RPM PTO			
Overall Length	9' 10"	12'	12'	14'	16' 6"	17' 6"
Overall Width	49.75"	60"	57"	65"	76"	80"
Loading Height	28"	33"	33"	36"	43"	45"
Tire Size	6/12	5.90/15	5.90/15	9.50/15	10/15 SL	11/22.5 SL
	Traction	Traction	IMPL	IMPL		
Weight	600 lbs	825 lbs	825 lbs	1,150 lbs	1,700 lbs	1,900 lbs

Specifications Subject To Change Without Notice